MRO800/1200

COMMERCIAL FILTRATION SYSTEM - TDS ADJUSTMENT



SYSTEM SPECIFICATION

Brand HydroNovation

Product Model HD-MRO800/1200

Produdct Dimensions (mm)

Size 1/2" -3/8" -1/4"

Inlet/Outlet Size (Inlet/Purified/Drain)

L500xW351xH855

Flow Rate (Model 800/1200) Min. 2L/min / 3L/min

Recovery Rate 55%

Working Pressure 0.1 - 0.4Mpa

Working Temperature 5−38℃
WiFi Connection Optional

Pre-filter 1 PP+GAC Cartridge

Pre-filter 2 UF Cartridge

Core Filtration 400/600 RO Membrane (2 pcs)

Post filter AFC Cartridge

MOH Certification v

NSF Standard NSF 58

Remove Particulates √

Remove Chlorine $\sqrt{}$

Remove Taste & Odor $\qquad \sqrt{}$

Remove Organic

Compound

Remove Turbidity 1

Reduce & Adjust TDS √

Remove Hardness √

Remove Bacteria

 \checkmark





Customization

Output TDS is adjustable based on customer requirements.



Space Saving

Small footprint, can be installed wall mounted or free standing.



Screen Display

Display shows input & output TDS, filter change reminder.



Two Water Outlets

One is TDS adjusted water, one is UF treated water(optional).